



TUPRW123 Wad

12 Gauge 3" Data for Steel Shot

⚠ WARNING

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.

©Copyright Precision Reloading, LLC. 2018

Cheddite 12 Gauge 3" Plastic Case with Plastic Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Ched 209	800X	23.5	TUPRW123	XYFE25020	1-1/8	1,223	11,180	123185
Ched 209	Blue Dot	33.0	TUPRW123	XYFE25020	1-1/8	1,336	11,250	123029
Ched 209	IMR Blue	32.5	TUPRW123	XYFE25020	1-1/8	1,225	11,490	123072
Ched 209	Universal	21.0	TUPRW123	XYFE25020	1-1/8	1,204	10,450	123163
Fed 209A	Steel	29.5	TUPRW123	XYFE25020	1-1/8	1,381	11,500	123096
Fiocchi 616	800X	24.0	TUPRW123	XYFE25020	1-1/8	1,214	11,030	123186
Fiocchi 616	Blue Dot	33.0	TUPRW123	XYFE25020	1-1/8	1,326	10,810	123030
Fiocchi 616	IMR Blue	32.5	TUPRW123	XYFE25020	1-1/8	1,226	11,050	123073
Fiocchi 616	Universal	21.0	TUPRW123	XYFE25020	1-1/8	1,200	10,500	123164
Ched 209	Blue Dot	28.5	TUPRW123		1-1/4	1,204	11,130	123050
Fed 209A	Steel	25.5	TUPRW123		1-1/4	1,230	11,230	123108
Fiocchi 616	Blue Dot	28.5	TUPRW123		1-1/4	1,212	11,480	123051

Federal 12 Gauge 3" Plastic Hull with Paper Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	800X	23.5	TUPRW123	XYFE25020	1-1/8	1,220	11,090	123187
Fed 209A	Blue Dot	32.0	TUPRW123	XYFE25020	1-1/8	1,359	11,490	123031
Fed 209A	IMR Blue	31.5	TUPRW123	XYFE25020	1-1/8	1,214	11,480	123074
Fed 209A	Steel	29.5	TUPRW123	XYFE25020	1-1/8	1,345	11,270	123097
Win 209	800X	24.0	TUPRW123	XYFE25020	1-1/8	1,223	11,010	123188
Win 209	Blue Dot	32.0	TUPRW123	XYFE25020	1-1/8	1,302	11,090	123032
Win 209	IMR Blue	31.5	TUPRW123	XYFE25020	1-1/8	1,205	11,280	123075
Fed 209A	Blue Dot	27.5	TUPRW123		1-1/4	1,204	11,480	123052
Fed 209A	Steel	24.5	TUPRW123		1-1/4	1,194	11,330	123109
Win 209	Blue Dot	28.0	TUPRW123		1-1/4	1,206	11,390	123053

Precision Reloading, LLC Hull Item Number - HLF123RH6

Insert Filler Wad Under Shot in Base of Wad.

Federal 12 Gauge 3" Plastic Unibody Hull

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	Blue Dot	31.0	TUPRW123	XYFE25020	1-1/8	1,308	11,420	123033
Win 209	Blue Dot	31.0	TUPRW123	XYFE25020	1-1/8	1,261	10,650	123034
Fed 209A	IMR Blue	30.5	TUPRW123	XYFE25020	1-1/8	1,215	11,430	123076
Win 209	IMR Blue	30.5	TUPRW123	XYFE25020	1-1/8	1,234	11,310	123077
Fed 209A	Steel	30.0	TUPRW123	XYFE25020	1-1/8	1,359	11,420	123098
Fed 209A	Steel	26.5	TUPRW123		1-1/4	1,255	11,320	123223

Precision Reloading, LLC Hull Item Number - HLF123UH6

Insert Filler Wad Under Shot in Base of Wad.

Reloading Notes

 **WARNING**

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.

Fiocchi 12 Gauge 3" Plastic Hull with Plastic Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Ched 209	800X	23.5	TUPRW123	XYFE25020	1-1/8	1,235	11,110	123189
Ched 209	Blue Dot	33.0	TUPRW123	XYFE25020	1-1/8	1,353	11,480	123035
Ched 209	IMR Blue	32.0	TUPRW123	XYFE25020	1-1/8	1,211	11,190	123078
Fed 209A	Steel	30.0	TUPRW123	XYFE25020	1-1/8	1,372	11,360	123099
Fiocchi 616	800X	24.0	TUPRW123	XYFE25020	1-1/8	1,225	11,010	123190
Fiocchi 616	Blue Dot	33.0	TUPRW123	XYFE25020	1-1/8	1,335	10,840	123036
Fiocchi 616	IMR Blue	32.0	TUPRW123	XYFE25020	1-1/8	1,217	11,300	123079
Ched 209	Blue Dot	28.5	TUPRW123		1-1/4	1,213	11,410	123054
Fed 209A	Steel	25.0	TUPRW123		1-1/4	1,247	11,410	123224
Fiocchi 616	Blue Dot	28.5	TUPRW123		1-1/4	1,204	11,490	123055

Precision Reloading, LLC Hull Item Number - FC123GA

Insert Filler Wad Under Shot in Base of Wad.

Remington 12 Gauge 3" Plastic Hull with Yellow Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	Blue Dot	30.0	TUPRW123	XYFE25020	1-1/8	1,282	11,500	123037
Fed 209A	IMR Blue	29.0	TUPRW123	XYFE25020	1-1/8	1,177	11,490	123080
Fed 209A	Steel	28.5	TUPRW123	XYFE25020	1-1/8	1,316	11,240	123100
Rem 209P	Blue Dot	30.5	TUPRW123	XYFE25020	1-1/8	1,252	10,290	123038
Win 209	Blue Dot	30.0	TUPRW123	XYFE25020	1-1/8	1,262	11,420	123039
Win 209	IMR Blue	29.5	TUPRW123	XYFE25020	1-1/8	1,220	11,380	123081

Precision Reloading, LLC Hull Item Number - HLR123PH6B, HLR123PH6G & HLR123PH6S

Insert Filler Wad Under Shot in Base of Wad.

Reloading Notes


WARNING

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.

Winchester 12 Gauge 3" Plastic Hull with Plastic Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	800X	22.5	TUPRW123	XYFE25020	1-1/8	1,203	11,080	123191
Fed 209A	Blue Dot	33.5	TUPRW123	XYFE25020	1-1/8	1,359	11,400	123040
Fed 209A	IMR Blue	33.5	TUPRW123	XYFE25020	1-1/8	1,267	10,880	123082
Fed 209A	Steel	32.5	TUPRW123	XYFE25020	1-1/8	1,426	11,500	123101
Win 209	800X	23.0	TUPRW123	XYFE25020	1-1/8	1,223	11,050	123192
Win 209	Blue Dot	33.5	TUPRW123	XYFE25020	1-1/8	1,301	9,870	123041
Win 209	IMR Blue	33.5	TUPRW123	XYFE25020	1-1/8	1,228	10,750	123083
Fed 209A	Steel	25.0	TUPRW123		1-1/4	1,229	11,190	123110

Precision Reloading, LLC Hull Item Number - HLW123PH6B & HLW123PH6R

Insert Filler Wad Under Shot in Base of Wad.

Reloading Notes

⚠ WARNING

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.